

Safety data sheet

FE 348-M B-RESIN

Revision date : 2007/03/01
Version: 4.4

Page: 1/6
(30245621/MDS_GEN_US/EN)

1. Substance/preparation and company identification

| | |
|--|---|
| <u>Company</u> | <u>24 Hour Emergency Response Information</u> |
| BASF Polyurethane Foam Enterprises LLC | CHEMTREC: 1-800-424-9300 |
| 13630 Watertower Circle | Hotline: 1-800-888-3342 |
| Minneapolis, MN 55441 | |

| | |
|------------------|---------------------------------|
| Chemical family: | resin |
| Synonyms: | URETHANE SYSTEM RESIN COMPONENT |

2. Composition/information on ingredients

| <u>CAS Number</u> | <u>Content (W/W)</u> | <u>Chemical name</u> |
|-------------------|----------------------|------------------------------|
| | < 75.0 % | Polyol |
| | < 12.0 % | Flame Retardant |
| 56-81-5 | < 2.0 % | glycerol |
| 108-01-0 | < 5.0 % | 2-dimethylaminoethanol |
| | < 2.0 % | Surfactant |
| | < 2.0 % | Catalyst |
| 460-73-1 | < 10.0 % | 1,1,1,3,3-pentafluoropropane |

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
SENSITIZER.
CONTAINS MATERIAL WHICH CAN CAUSE NERVOUS SYSTEM DAMAGE.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Ingestion may cause gastrointestinal disturbances.

Information on: Fluorocarbons

At levels above the recommended exposure limit, the fluorocarbon acts as a weak narcotic. Acute overexposure causes tremors, confusion, irritation, suffocation, and may result in cardiac sensitization.

Safety data sheet

FE 348-M B-RESIN

Revision date : 2007/03/01

Version: 4.4

Page: 2/6

(30245621/MDS_GEN_US/EN)

Information on: Dimethylaminoethanol

Dimethylaminoethanol is extremely irritating to the skin and eyes. Direct contact with the liquid is corrosive. Acute inhalation exposures at high concentrations have been known to produce respiratory difficulties, loss of coordination and decreased motor activity in rats.

Information on: Glycerin

Ingestion of large amounts of glycerine may result in nausea, vomiting, gastric irritation, and kidney disorders. Glycerine can exert systemic effects when given orally in very large doses.

Irritation:

Irritating to respiratory system.

Information on: Polyol

Contact with the eyes and skin may result in irritation.

Information on: Dimethylaminoethanol

Contact with dimethylaminoethanol may result in severe irritation. Burns and permanent injury may result.

Repeated dose toxicity:

Information on: Dimethylaminoethanol

Repeated skin contact with dimethylaminoethanol may result in sensitization. Repeated inhalation has been known to produce effects on the eyes and nasal mucosa as well as respiratory and olfactory lesions in experimental animals. Exposure to dimethylaminoethanol has been associated with visual and ocular changes and is reversible upon significantly reduced or ceased exposure.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. Immediate medical attention required.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Immediate medical attention required.

5. Fire-fighting measures

Flash point:

> 200 °F

(closed cup)

Autoignition:

No data available.

Suitable extinguishing media:

water, dry extinguishing media, carbon dioxide, foam

Hazards during fire-fighting:

No particular hazards known.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Safety data sheet

FE 348-M B-RESIN

Revision date : 2007/03/01
Version: 4.4

Page: 3/6
(30245621/MDS_GEN_US/EN)

6. Accidental release measures

Cleanup:

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and storage

Handling

General advice:

Product should not be mixed with air above atmospheric pressure for leak testing or any other purpose. Use dry nitrogen to transfer or leak test equipment pressurized with product.

Protection against fire and explosion:

No explosion proofing necessary.

Storage

General advice:

Product that is frozen and/or tending to sedimentation can be liquified or homogenized by careful application of indirect heat (do not use flames or direct contact with a heat source). Protect from direct sunlight. Keep in a cool, well-ventilated place. Avoid extreme heat. Store protected against freezing. Stored and transported in a cylinder under pressure. Must not be repacked by the customer.

Storage stability:

Storage temperature: 50 - 80 °F

Protect against moisture. Store in unopened original containers in a cool and dry place.

8. Exposure controls and personal protection

Components with workplace control parameters

| | | |
|----------|-------|--|
| glycerol | OSHA | PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; |
| | ACGIH | TWA value 10 mg/m3 Mist ; |

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

Safety data sheet

FE 348-M B-RESIN

Revision date : 2007/03/01

Version: 4.4

Page: 4/6

(30245621/MDS_GEN_US/EN)

9. Physical and chemical properties

| | | |
|-------------------------|---------------------|------------------|
| Form: | liquid | |
| Odour: | amine-like | |
| Colour: | dark brown | |
| Relative density: | 1.22 | |
| Bulk density: | 9.82 - 10.33 lb/USg | (25 °C) |
| Viscosity, dynamic: | 1,100 - 1,400 | (23 °C) |
| | mPa.s | |
| Miscibility with water: | | slightly soluble |

10. Stability and reactivity

Conditions to avoid:

> 80 degrees Fahrenheit

Avoid moisture. Avoid direct sunlight. Avoid excessive temperatures.

Hazardous reactions:

The product is chemically stable.

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide

Thermal decomposition:

No data available.

Corrosion to metals:

No corrosive effect on metal.

11. Toxicological information

12. Ecological information

13. Disposal considerations

Waste disposal of substance:

Incinerate in a licensed facility.

Dispose of in a licensed facility.

Do not discharge substance/product into sewer system.

Container disposal:

DRUMS:

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers).

Decontaminate containers prior to disposal. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport information

Land transport

USDOT

Safety data sheet

FE 348-M B-RESIN

Revision date : 2007/03/01
Version: 4.4

Page: 5/6
(30245621/MDS_GEN_US/EN)

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US released / listed

TSCA 12B released / listed

State regulations

State RTK

| <u>CAS Number</u> | <u>Chemical name</u> | <u>State RTK</u> |
|-------------------|------------------------|------------------|
| 56-81-5 | glycerol | MA, PA |
| 108-01-0 | 2-dimethylaminoethanol | MA, NJ, PA |

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

16. Other information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 1

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

1-800-888-3342

Safety data sheet

FE 348-M B-RESIN

Revision date : 2007/03/01

Page: 6/6

Version: 4.4

(30245621/MDS_GEN_US/EN)

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF POLYURETHANE FOAM ENTERPRISES LLC HEREUNDER ARE GIVEN GRATIS AND BASF POLYURETHANE FOAM ENTERPRISES LLC ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET