



# ALDOCOAT 914

## METAL TOP COAT

### TYPICAL PHYSICAL PROPERTIES

COVERAGE RATE.....	65 – 100 SF/GAL
FLASHPOINT.....	101°F
WEIGHT (LB./GAL.).....	8.6
SOLIDS (% BY WEIGHT).....	51.0±1%
VISCOSITY @ 78°.....	4000 CPS
DRYING TIME.....	2 – 4 HOURS
ELONGATION.....	400%
TENSILE STRENGTH....	ASTM D-412...1500 PSI

### **Recommended Spray Equipment = Airless**

TIP SIZE.....	0.025"
FLUID PRESSURE (PSI).....	3000
FLUID HOSE SIZE.....	3/8" – 1/2"

### PRODUCT DESCRIPTION

---

**ALDOCOAT 914 Metal Top Coat** provides excellent waterproofing and ultraviolet resistance. It is a one-component product that has excellent adhesion to properly prepared surfaces. It is thermally stable and resists cracking and peeling due to weather extremes. **ALDOCOAT 914** is the primary top coat for **ALDOBASE 913**.

### GENERAL SURFACE PREP

---

The surface must be free of any oils, moisture, soil or other contaminants that may interfere with good adhesion. Remove any loose material from seams or other surfaces. Oil and grease should also be removed with solvents or an appropriate detergent cleaner. In many cases high pressure water blast will be sufficient to prepare the surface.

For best results, apply **ALDOCOAT 914** when ambient air and the substrate is within 50 – 100°F. For best spray application, the product should be at a minimum of 60°F. Lower temperatures can be utilized for brush.

**ALDOCOAT 914** can be applied by brush, spray or roller. Best results can be obtained with airless spray equipment.

### LIMITATIONS AND PRECAUTIONS

---

**ALDOBASE 913** contains a blend of solvents which is considered combustible by D.O.T. and O.S.H.A. standards. It should be used and stored away from flames, in a well-ventilated atmosphere. Avoid prolonged breathing of vapors and prevent contact with eyes. Read all label information and precautions before using.

The specifications, properties and performance of materials described herein are based on information believed to be reliable. Unless otherwise expressly provided in written contract, the products discussed are sold without conditions or warranties, expressed or implied. Product specifications are subject to change without notice.